To appear in ORSA Journal on Computing.

Computational Experience with an Approximation Algorithm on Large-Scale Euclidean Matching Instances

David P. Williamson
IBM TJ Watson Research Center
Yorktown Heights, NY 10598
(914) 945-1743
dpw@watson.ibm.com

Michel X. Goemans
Department of Mathematics
MIT
Cambridge, MA 02139
(617) 253-2688
goemans@math.mit.edu

Abstract

We consider a 2-approximation algorithm for Euclidean minimum-cost perfect matching instances proposed by the authors in a previous paper. We present computational results for both random and real-world instances having between $1,000$ and $131,072$ vertices. The results indicate that our algorithm generates a matching within 2% of optimal in most cases. In over 1,400 experiments, the algorithm was never more than 4% from optimal. For the purposes of the study, we give a new implementation of the algorithm that uses linear space instead of quadratic space, and appears to run faster in practice.

Subject classification:

- Networks/graphs, matchings: experimental analysis of heuristics
- Analysis of algorithms: experimental analysis

The main criticism which is often formulated with regard to approximation algorithms is that, although they are backed up by a performance guarantee (often through very elegant arguments), they might not generate "nearly-optimal" solutions in practice. Indeed, a practitioner will seldom be satisfied with a solution guaranteed to be of cost less than, say, twice the optimum cost; by far, he will prefer a heuristic algorithm which typically generates a solution within, say, 3% of optimality, although this heuristic might from time to time generate a more costly solution. For example, in the context of the traveling salesman problem, computational studies show that the heuristic algorithm of Lin and Kernighan outperforms in practice the algorithm of Christofides, although the latter one has a performance guarantee of $\frac{3}{2}$ (i.e., the cost of Christofides' tour is guaranteed to be within a factor of $\frac{3}{2}$ of optimal) [8]. A similar comment can be made for running times both for exact or approximation algorithms. The fastest algorithm in practice might not be the one with best *worst-case* running time.

Motivated by these comments, we perform a computational study of an existing approximation algorithm for the Euclidean minimum-cost perfect matching problem. The minimum-cost perfect matching problem is the problem of finding a minimum-cost set of non-adjacent edges that cover all vertices. The algorithm we consider was proposed by Goemans and Williamson [11] for any cost function satisfying the triangle inequality, but we restrict our attention to Euclidean instances where the edge costs are the distances between points under the l_2 or l_∞ norms. The algorithm has a performance guarantee of 2, and the implementation described in [11] runs in $O(n^2 \log n)$ time, where n denotes the number of vertices. The algorithm has an important feature from a practical point-of-view: it is primal-dual. This means that it not only generates a perfect matching but also a lower bound on the optimum cost. The worst-case result proved in [11] says that the cost of the perfect matching generated is at most twice the value of the lower bound generated by the algorithm.

The main purpose of this computational study is to determine how far the perfect matching obtained by the algorithm is from optimal. Our results thus far indicate that in terms of quality of approximation, the algorithm behaves more like Lin-Kernighan's algorithm than Christofides': in over 1,400 experiments on random and structured instances ranging in size from 1,000 to 131,072 vertices, the algorithm was never more than 4% away from optimal and 7% away from the lower bound. On random instances drawn uniformly from the unit square, a result of Papadimitriou [16] shows that the cost of an optimal matching on n vertices almost surely converges to $\beta_M \sqrt{n}$, where β_M is constant. Assuming that our algorithm has the same behavior, we show experimentally that the matching constant for the algorithm is 1.6% away from β_M and 3.7% away from the constant of the lower bound when the Euclidean norm is used. When the l_∞ norm is used, these gaps become 2.0% and 4.4%. In the course of obtaining these results, we also obtain a new estimate of β_M. On several structured instances drawn from the Traveling Salesman Library, TSPLIB [18], the algorithm performed somewhat better than on random instances, generating matchings at most 2% away from optimal and usually within 1–1.5%.

For the purposes of this study, it was necessary to develop a different implementation of the algorithm than that given in Goemans and Williamson [11]. The main drawback of the implementation given there is that it requires $\Theta(n^2)$ space. This space bound severely limits the size of the instances that could be solved. Using some algorithmic ideas of Bentley and Friedman [6] and Bentley [5], we give an implementation that uses $O(n)$ space. Our implementation also seems to be faster in practice, although its worst-case running time, while still polynomial, is not as good as $O(n^2 \log n)$.

In addition to studying the quality of solutions produced by the algorithm, we report other various statistical properties of the solutions and of the algorithm's implementation.

Our study to this point does not yet answer the question of whether the approximation algorithm is a practical alternative to a very good implementation of an algorithm that can solve the matching problem exactly or to other heuristics for the matching problem. Edmonds [7] first showed that the matching problem is solvable in polynomial time, and since then several algorithms and implementations of these algorithms have been proposed; see Applegate and Cook [1] for a brief discussion. For our study, we used a very efficient implementation of Edmonds' algorithm written by Applegate and Cook [1] to find optimal matchings. Our implementation was only faster than Applegate and Cook's code on large random instances; it was slightly slower on small random and structured instances and usually significantly slower on large structured instances. It is likely that a speed-up of our implementation can be achieved if we first restrict our attention to a sparse subgraph as is done by Applegate and Cook. In addition, other matching heuristics described in the literature (such as that of Jünger and Pulleyblank [14] and those in the survey of Avis [2]) run much faster, although the quality of the solutions produced does not appear to be as good and the heuristics have no worst-case performance guarantee.

Our abstract is structured as follows. In Section 1, we review the approximation algorithm of Goemans and Williamson [11]. Section 2 discusses the new implementation, and Section 3 reviews known results about the behavior of Euclidean optimization problems on random instances that prompted some of our computational study. Section 4 gives the results of our study, and we conclude with some remarks in Section 5.

1 Review of the algorithm

In this section, we review the algorithm of Goemans and Williamson [11] and we also briefly indicate an implementation running in $O(n^2 \log n)$ time.

The algorithm is shown in Figure 1. The main portion of the algorithm (lines 1 through 12) finds a set F' of edges such that every vertex has odd degree and, thus, each connected component has even size. This part of the algorithm maintains a forest F of edges, which is initially empty. The algorithm loops, in every iteration selecting an edge (i, j) between two distinct connected components of F, then merging these two components by adding (i, j) to F. The loop terminates when all connected components C of F have even size. From these edges in F, we form the set F' of edges by keeping only necessary edges. Thus we remove any edge from F that joins two components of even size. A parity argument shows that every vertex in the resulting set must have odd degree.

The final step of the algorithm (line 13) turns the set of edges F' into a perfect matching. A matching of cost no greater than F' can be obtained as follows: duplicate all edges in F' so that each component is an Eulerian graph on an even number of vertices, shortcut each component to a cycle, then keep the best matching out of the two induced by the cycle. To obtain slightly better matchings, we find the optimal matching on the component by complete enumeration for all components of size 10 or smaller, and use the doubling-and-shortcutting method for larger components.

The good approximation properties of the algorithm follow from the way in which the edge is chosen in each iteration. The algorithm maintains variables $d(v)$ for each vertex v, and a lower bound LB; these variables are all initially zero. In each iteration, the algorithm chooses an edge $e = (i, j)$ spanning

Input: A complete graph $G = (V, E)$ and edge costs $c_e \geq 0$ satisfying the triangle inequality
Output: A perfect matching M and a value LB

$F \leftarrow \emptyset$
$LB \leftarrow 0$
$\mathcal{C} \leftarrow \{\{v\} : v \in V\}$
For each $v \in V$
  $d(v) \leftarrow 0$
While $\exists C \in \mathcal{C} : |C|$ is odd
  Find edge $e = (i, j)$ with $i \in C_p \in \mathcal{C}$, $j \in C_q \in \mathcal{C}$, $C_p \neq C_q$ that minimizes $\epsilon = \frac{c_e - d(i) - d(j)}{p(C_p) + p(C_q)}$
  $F \leftarrow F \cup \{e\}$
  For all $v \in C_r \in \mathcal{C}$ do $d(v) \leftarrow d(v) + \epsilon \cdot p(C_r)$
  $LB \leftarrow LB + \epsilon \sum_{C \in \mathcal{C}} p(C)$
  $\mathcal{C} \leftarrow \mathcal{C} \cup \{C_p \cup C_q\} - \{C_p\} - \{C_q\}$
$F' \leftarrow \{e \in F :$ There exists an odd connected component N in $(V, F - \{e\})\}$
Convert F' to matching M. For each component of F', duplicate all the edges of F', shortcut in order to obtain a collection of cycles and, for each such cycle, keep the best matching out of the two that it induces. Find optimal matchings on small components.

Figure 1: The main algorithm.

two distinct components (say C_p and C_q) that minimizes $\epsilon = \frac{c_e - d(i) - d(j)}{p(C_p) + p(C_q)}$, where $p(C)$ is the parity of component C (that is, 1 if C has odd size, and 0 otherwise). It can be shown that $\epsilon \geq 0$. Then $d(v)$ is increased by ϵ for all vertices v in odd components, and LB is increased by ϵ times the number of odd components. Goemans and Williamson [11] show that choosing the edges in this fashion implicitly constructs a feasible solution to the dual of a linear programming formulation of the matching problem such that the value of the dual solution is LB, and $\sum_{e \in F'} c_e \leq 2\,LB$. Because LB is a lower bound on the value of an optimal matching, this proves that the algorithm has a performance guarantee of 2.

The main problem involved in implementing the algorithm is deciding which edge to select in each iteration. The $O(n^2 \log n)$ time algorithm of [11] uses a priority queue of edges. Given a notion of *time* T in the algorithm (starting at zero and advancing by ϵ each iteration), the key value of each edge $e = (i, j)$ is $T + \frac{c_e - d(i) - d(j)}{p(C_p) + p(C_q)}$. We call this quantity the edge's *addition time*; it is the time at which the reduced cost $\frac{c_e - d(i) - d(j)}{p(C_p) + p(C_q)}$ of the edge will be zero, given that the parity of the two components containing its two endpoints remains the same. Since the parity of components change only when two components are merged, we only need to update the key values of edges adjacent to the two components that are merged. Also, for each pair of components we only need to keep the edge with the smallest addition time. We select the edge with the smallest addition time in each iteration. This analysis leads to $O(n)$ queue operations per iteration of the algorithm, with $O(n)$ iterations, for an overall running time of $O(n^2 \log n)$. Gabow, Goemans, and Williamson [10] have shown how this selection step can be implemented in $O(n^2 \sqrt{\log \log n})$ time by using many small priority queues.

2 Implementation Description

In this section, we describe another implementation of the edge selection step. The implementation described in the previous section has two main disadvantages for performing computational experiments. The first is that it uses $\Theta(n^2)$ space; this severely limits the size of the instances that can be solved.

The second is that the running time is in fact $\Theta(n^2 \log n)$: the algorithm must add at least $n/2$ edges to obtain a feasible solution, necessitating $\Theta(n^2)$ queue operations. The main theoretical advantage of our new implementation compared to the one given above is that it is much more space efficient, using only $O(n)$ space. Moreover, although its worst-case time complexity appears to be worse than the original implementation, it performs well enough on average to allow us to run relatively large instances. It will require $O(n^2)$ queue operations, and we will see experimentally that it requires $O(n^{1+\epsilon})$ queue operations on random instances, although other factors will now dominate the running time.

Before we go on to describe the main idea behind selecting edges in our implementation, we note that several small tricks are necessary to ensure that other parts of the algorithm do not force the running time to be $\Omega(n^2)$. For example, updating the $d(v)$ variables each iteration would take $\Theta(n^2)$ time. To avoid this, we augment a union-find structure used to keep track of the connected components of the current edge set. Since the $d(v)$ are increased by the same amount for all vertices v in the same component, we increase an offset in the root of the component, and define $d(v)$ to be the sum of the offsets along the path to the root. In addition, we let the increases for a component accumulate and only change the offset when we merge the component with another component, or when we need to calculate $d(i)$ for some vertex i in the component.

The basic idea of the implementation is that each component should maintain an estimate of its closest neighboring component under addition times. The corresponding edges are placed in a priority queue with the estimates as the key values. The estimates are maintained in such a way that the shortest edge (under addition times) between two components is always found in any iteration of the while loop; thus the algorithm can be successfully implemented. The main advantage of this implementation is its space efficiency: we need to keep track of the keys of only $|\mathcal{C}|$ edges, where $\mathcal{C}$ is the set of components. This approach is adapted from algorithms for the minimum-cost spanning tree and traveling salesman problems in Bentley and Friedman [6] and Bentley [5].

More formally, let $l(e)$ denote the current addition time of edge $e = (i, j)$. For two components C_p and C_q in $\mathcal{C}$, let $l(C_p, C_q)$ be equal to the smallest addition time of an edge with one endpoint in C_p and the other in C_q. The key of an edge e in the queue will be denoted by $k(e)$ and corresponds to the addition time of that edge when it was added to the queue. By abuse of notation, we let $k(C)$ denote the key of the edge in the queue which was selected by component C.

The implementation works as follows:

- Initially, every vertex calculates its nearest neighbor (under addition times) and puts the corresponding edge in the priority queue with a key value of the addition time.
- Whenever we pull an edge e off the queue, we check if its key value $k(e)$ is no less than its actual addition time $l(e)$. We maintain that whenever this is true, then the edge is the next edge that should be added; that is, it has the smallest addition time. Whenever two components get merged into one, we find its new nearest neighbor under addition times.
- When the key value of the edge e is less than the actual addition time, we then search for the component's real nearest neighbor, bounding the search by the correct addition time $l(e)$ of e, and insert the corresponding edge in the priority queue with its correct key value.

In order to prove that the implementation is correct, we first prove that it maintains an invariant.

Lemma 2.1 At any point in the algorithm, for all $C_p, C_q \in \mathcal{C}$, $\min(k(C_p), k(C_q)) \leq l(C_p, C_q)$.

Proof: Certainly the invariant is true initially. Suppose that we insert an edge e selected by component C to the queue. This insertion might be the result of either two components merging into C or the discovery that the edge in the queue corresponding to C has a key less than its addition time. In both cases, the invariant is maintained for any two components C_p and C_q different from C. Moreover, if $C_p = C$ then our choice of the edge to insert guarantees that $\min(k(C), k(C_q)) \leq k(C) = k(e) = l(e) \leq l(C, C_q)$, implying that the invariant continues to hold. ■

The invariant leads to a proof of correctness.

Theorem 2.2 The implementation selects an edge with the smallest addition time in every iteration.

Proof: In each iteration of the algorithm, we must find the edge with the smallest addition time. Let a denote the smallest addition time of this iteration, and let e be the edge at the top of the queue. We will show that whenever $k(e) \geq l(e)$ then $l(e) = a$ and thus the algorithm correctly selects edge e. Whenever $k(e) < l(e)$ we replace the queue element e with another edge e' such that $k(e') = l(e')$. Such a replacement does not affect the distances between components or the other key values in the queue, so we can replace at most $|\mathcal{C}|$ number of edges before we must reach the case that $k(e) \geq l(e)$ for the top element e of the queue.

Suppose $k(e) \geq l(e)$. By the invariant, for any $C_p, C_q \in \mathcal{C}$, we have $\min(k(C_p), k(C_q)) \leq l(C_p, C_q)$. But since e is the edge at the top of the queue, $k(e) \leq k(C)$ for all $C \in \mathcal{C}$ and, thus, $k(e) \leq l(C_p, C_q)$. The fact that $l(e) \leq k(e)$ now implies that $l(e) \leq l(C_p, C_q)$ for any $C_p, C_q \in \mathcal{C}$. In other words, e is an edge with smallest addition time. ■

We now evaluate the worst-case number of queue operations. The argument of the theorem shows that we perform at most $O(n)$ queue operations for each edge selection. This implies that the algorithm performs a total of $O(n^2)$ queue operations.

In order to complete the description of our implementation, we must describe how to find an edge e that represents the nearest neighbor of a component C under addition time. To do this, we use *k-d* trees of Friedman, Bentley, and Finkel [9] as described in Bentley [4]. A *k-d* tree is a binary tree that corresponds to a partitioning of a given set of points in d-dimensional space; here we use $d = 2$. The tree is constructed by determining whether the points are spread out most in the x or y direction, then finding the vertical or horizontal line that splits the points in half in that direction. The line determines an internal node of the tree, and the procedure is performed recursively on each half until the number of points remaining is below a certain threshold (usually 5 or 6). Hence each leaf in the tree corresponds to a bucket containing at most a certain number of points. The tree can be used to perform a search for the nearest neighbor of a given point under a number of norms (including L_1, l_2 and l_∞): at each internal node we first search the subtree containing the given point, then search the other tree if the nearest neighbor found so far is no closer than the distance from the given point to the line determining the internal node. Friedman et al. show experimentally that this search takes $O(\log n)$ expected time, and Bentley [4] gives a bottom-up variation that seems to take $O(1)$ expected time. Notice that this search method also lends itself to searching for the nearest neighbor within a certain radius.



Figure 2: The four quadrants around v_i.

To find the nearest neighbor of a component C under addition time, we iterate through the vertices in C to find the smallest edge (under addition time) from the vertex to a vertex not in C. We use the smallest edge found so far to bound the search on the next vertex. Let v_i denote the point in the Euclidean plane corresponding to vertex i, and let $||v_i - v_j||$ denote the distance between vertices i and j, and hence the cost of edge (i, j). Suppose we are searching from vertex i in component C, the current time is T, and the smallest edge found so far has addition time a. Thus any potentially smaller edge $e = (i, j)$ must satisfy $T + \frac{c_e - d(i) - d(j)}{p(C)+p(C')} \leq a$, which implies that $c_e - d(i) - T \leq (a - T)(p(C) + 1)$ since $d(j) \leq T$ for all $j \in V$ and $p(C') \leq 1$. Therefore j must be within distance $(a - T)(p(C) + 1) + d(i) + T$.

As one might suspect, the time spent performing these searches dominates all other operations in our implementation. Therefore, we introduce a few tricks for speeding up these searches. The first trick is that whenever we notice that all the vertices in a subtree of the k-d tree belong to the same component, we label the subtree with the name of that component. Then whenever we search for the nearest neighbor of a vertex in C, we ignore all subtrees labelled C. This trick is useful as C becomes large and most of the neighboring vertices of a given vertex in C are also in C.

Another trick we use is that when searching for the nearest neighbor of a vertex i in C, we can sometimes infer when possible nearest neighbor candidates will be closer to another vertex j in C than i. We say that i is *shadowed* by j. Thus we can disregard these nearest neighbor candidates. To be more formal, consider the four quadrants of the plane formed by using v_i as the origin. Let (x_i, y_i) denote the coordinates of v_i. Let n_i be the Euclidean point $(x_i + d(i), y_i)$ and let e_i be the point $(x_i, y_i + d(i))$ (see Figure 2).

Theorem 2.3 Suppose there is some other vertex j in C such that j is not in quadrant III (i.e. j is such that $x_j \geq x_i$ or $y_j \geq y_i$), and

$$||n_i - v_j|| \leq d(j) \text{ and } ||e_i - v_j|| \leq d(j).$$

Then, for any vertex q in quadrant I ($x_q \geq x_i$ and $y_q \geq y_i$) that is in component $C' \neq C$, vertex j is at least as close to vertex q under addition times as is vertex i.

Proof: To show this, we will prove that $||v_q - v_j|| - d(j) \leq ||v_q - v_i|| - d(i)$. From this it will follow that $T + \frac{||v_q - v_j|| - d(j) - d(q)}{p(C)+p(C')} \leq T + \frac{||v_q - v_i|| - d(i) - d(q)}{p(C)+p(C')}$.



Figure 3: Illustration of the case in which v_q is in quadrant I.

We consider two cases. First suppose that v_j is in quadrant I. Because vertex q is not in component C, it cannot lie inside the triangle defined by v_i, n_i and e_i. Furthermore, v_q cannot lie inside the triangle defined by v_j, n_i and e_i since both n_i and e_i are within distance $d(j)$ of v_j. As a result, the line segment (v_q, v_i) must intersect either the line segment (n_i, v_j) or the line segment (v_j, e_i) (see Figure 3). Assume the former (the other case is similar), and let m be the intersection point. Then

$$\begin{aligned} & ||v_i - v_q|| + ||v_j - n_i|| \\ = \;& ||v_i - m|| + ||m - n_i|| + ||v_q - m|| + ||m - v_j|| \\ \geq \;& ||v_i - n_i|| + ||v_q - v_j||, \end{aligned}$$

which implies that $||v_q - v_i|| + d(j) \geq ||v_q - v_j|| + d(i)$, as desired.

Now suppose that v_j is in quadrant IV (the case for II is similar). Since $||v_i - v_j|| \leq ||n_i - v_j|| \leq d(j)$ and v_q is not in the same component as v_i and v_j, v_q cannot be in the triangle defined by v_i, v_j, and n_i. Hence, the line segments (v_q, v_i) and (n_i, v_j) must intersect. Then the proof is the same as above. ■

Thus if vertex i is shadowed as in the statement of the theorem, we need not look for nearest neighbors of i in quadrant I. Obviously, shadowing is symmetric with respect to quadrants. Once the size of a component has increased by a certain amount, we sweep through the component, determining in which quadrants each vertex is shadowed. We store this information in four bits for each vertex and use it when we perform nearest neighbor searches to cut down the scope of the search for each vertex. If a vertex is shadowed in all four quadrants, then we do not perform a search on it at all.

3 Probabilistic Analysis of Euclidean Functionals

A great deal is known about the behavior of randomly distributed Euclidean instances of combinatorial optimization problems. In the basic version of the *Euclidean model*, the vertices of the problem instance are distributed independently and uniformly in the unit square $[0, 1]^2$ and the Euclidean metric plays the role of cost function. The *functionals* of interest are typically the values of combinatorial optimization problems (such as the traveling salesman, matching or minimum spanning tree problems) on these randomly distributed points. The behavior of these functionals is somewhat independent of the functional itself and, for these reasons, we briefly review some of these probabilistic results for the most studied problem, the traveling salesman problem. We also indicate results likely to hold, although they have never been proved. For a more detailed picture of the field, the reader is referred to [23, 15, 21, 27].

The asymptotic behavior of the value of the traveling salesman problem was first studied in the pioneering paper of Beardwood, Halton and Hammersley [3]. They prove the existence of a constant β_{TSP} such that

$$\lim_{n\to\infty} \frac{TSP_n}{\sqrt{n}} = \beta_{TSP} \qquad \text{almost surely} \tag{1}$$

where TSP_n denotes the value of the optimal tour on $X_1, X_2, \ldots, X_n$ with the X_i's being an infinite sequence of independently and uniformly distributed vertices from $[0,1]^2$. Steele has shown that $TSP_n/\sqrt{n}$ converges completely to β_{TSP} rather than almost surely [22]. We should point out that the exact value of β_{TSP} is not known. More recently, a careful analysis of the functional has led to the following results and/or conjectures. It is known that Var TSP_n is upper bounded by a constant (see Steele [22]): Var $TSP_n \leq \frac{16}{\pi} + O(\frac{1}{n})$. Quoting Steele [21],

> it seems inevitable that one has a genuine limit, $\lim_{n\to\infty} \text{Var}\, TSP_n = \sigma^2 > 0$. It is less certain but (still very likely) that one has a central limit theorem $TSP_n - E[TSP_n] \sim N(0, \sigma^2)$.

Rhee and Talagrand [20] have proved a first step towards this central limit theorem by showing that the tails of TSP_n are Gaussian or subGaussian: there exists K such that, for all t, $Pr\left(|TSP_n - E[TSP_n]| > t\right) \leq Ke^{-t^2/K}$. From the knowledge of $E[TSP_n]$ for a finite value of n, one can derive a bound on the limiting constant β_{TSP}. Indeed (see Jaillet [13]), there exists a constant $\gamma_{TSP} < 9.5$ such that, for all n, $|E[TSP_n] - \beta_{TSP}\sqrt{n}| \leq \gamma_{TSP}$. Furthermore, it seems likely that there exists a limit α_{TSP} such that $\lim_{n\to\infty} |E[TSP_n] - \beta_{TSP}\sqrt{n}| = \alpha_{TSP}$.

Some of these results also hold for other functionals; see Steele [23], Yukich [27], and the references above. For the minimum-cost perfect matching problem and its associated functional M, the asymptotic behavior (1) is known to hold (Papadimitriou [16]), and has also been strengthened to complete convergence (Redmond and Yukich [17]). The other results and/or conjectures seem likely to be true as well.

From these results and/or conjectures, we shall implicitly assume for our experimental study that, for several functionals L, L_n is normally distributed with mean $\beta_L\sqrt{n} + \alpha_L$ and variance σ_L^2. These functionals are the values of the minimum-cost perfect matching, and also of F', the perfect matching and the dual solution returned by our approximation algorithm. We shall denote these additional functionals by F', P (for primal) and D (for dual).

Functionals of a more structural nature have also been studied. For example, Steele et al. [24] have shown that there exist constants ν_k such that the number of degree k vertices in a minimum spanning tree divided by n is almost surely equal to ν_k. It is known that $\nu_k = 0$ for $k \geq 6$.

Problem Name	Norm	LBGAP	OPTGAP	Time	AC Time
r1002	l_2	4.59	1.54	3.57	2.69
r2392	l_2	3.57	.98	7.38	11.51
pcb3038	l_2	2.98	.93	30.32	22.26
rl5934	l_2	2.37	.93	326.30	119.85
pla7396	l_2	1.72	.94	461.25	203.11
rl11848	l_2	2.87	1.18	944.60	229.82
d18512	l_2	3.57	1.64	3651.13	664.93
r20726	l_∞	4.40	1.88	718.95	4636.06
pla33810	l_2	2.14	1.69	24687.20	1704.09
pla85900	l_∞	1.52	1.34	107653.81	6202.22

Table 1: Experimental results on TSPLIB instances.

4 Results

We summarize our main experimental results in a sequence of tables. Table 1 contains our results on the TSPLIB examples. Tables 2 and 3 contain our results on random instances; the first table is for instances using the l_2 norm, and the second is for instances using the l_∞ norm. The columns LBGAP and OPTGAP give the percentage excess of the approximate matching over the cost of the dual lower bound and over the cost of an optimal matching respectively. For instance, the approximate matching found for the r1002 TSPLIB instance was 4.59% more than the cost of the dual lower bound, and 1.54% more than the cost of the optimal matching. The Time column specifies the running time of the approximation algorithm, while the AC Time column specifies the running time of the Applegate and Cook algorithm for finding optimal matchings. We used the variation of the Applegate and Cook code which begins with a fractional 10 nearest neighbor graph. All running times are in CPU seconds on a Silicon Graphics Challenge machine with eight 100Mhz MIPS R4400 processors. The Speedup column gives the ratio of the running time of Applegate and Cook's algorithm to the running time of the approximation algorithm. We summarize our estimates of the parameters β and α in Table 4. We include for comparison parameters given for other matching heuristics. Finally, some asymptotic estimates of structural properties of the solutions are given in Table 5. Each of these tables is discussed in the following paragraphs. Some sample runs of the algorithm are shown in Figures 4 to 7.

The structured examples in Table 1 were taken from the TSPLIB [18]. The number in the problem name indicates the number of vertices in the problem. We attempted to use the same procedure as given in Applegate and Cook [1]; namely, if the example contained an odd number of points, we sorted by x and y coordinates, then deleted the last point. We also attempted as much as possible to run the same suite of examples as given in [1].

The random examples in Tables 2 and 3 were generated on a 2^{20} by 2^{20} grid using the UNIX `random()` function. A single seed was used to generate all the instances of a given size. The first entry of Table 2 comes from a sequence of 1000 experiments run separately on a VAX 9000 (11 data points had to be omitted). We used these experiments to get an upper bound on the variance of the matching parameters for F', P, D, and M on the unit square. Using the parameter with the largest variance (F'), we obtained an upper bound of .05399. This information was used to decide the number of experiments to perform in order to obtain small confidence intervals on the parameters β. We did not use the 1000 experiments

Size	Trials	Ave LBGAP	Ave OPTGAP	Max LBGAP	Max OPTGAP	Ave Time	Ave Speedup
2^{10}	989	3.69	1.59	5.87	3.46	–	–
2^{10}	64	3.69	1.58	6.15	3.67	5.09	.92
2^{11}	64	3.69	1.60	4.86	2.45	21.60	.92
2^{12}	32	3.72	1.65	5.00	2.65	79.75	1.12
2^{13}	32	3.61	1.57	4.34	2.08	261.59	1.72
2^{14}	16	3.68	1.63	3.90	1.89	1330.69	2.17
2^{15}	16	3.71	1.65	4.00	1.89	7533.67	2.00
2^{16}	8	3.70	1.64	3.79	1.79	32942.70	2.00
2^{17}	4	3.74	1.63	3.83	1.70	200820.00	1.87

Table 2: Experimental results on random instances using the l_2 norm.

Size	Trials	Ave LBGAP	Ave OPTGAP	Max LBGAP	Max OPTGAP	Ave Time	Ave Speedup
2^{10}	64	4.40	1.90	6.44	3.82	4.04	.73
2^{11}	64	4.40	1.97	5.64	2.89	14.86	.87
2^{12}	32	4.40	2.01	5.26	2.65	53.15	1.27
2^{13}	32	4.40	1.97	5.14	2.54	246.27	1.73
2^{14}	16	4.33	1.95	4.56	2.22	885.21	2.79
2^{15}	16	4.35	1.96	4.52	2.13	4577.87	2.95
2^{16}	8	4.46	2.05	4.70	2.23	28017.50	2.16
2^{17}	4	4.45	1.97	4.51	2.03	150841.00	3.19

Table 3: Experimental results on random instances using the l_∞ norm.



Figure 4: Snapshot of the algorithm working on a random instance of 500 vertices. The circle around each vertex i is of radius $d(i)$. Intuitively the algorithm expands these circles by ϵ in each iteration, causing two circles to touch. The edge (i,j) corresponding to these circles is then selected.